

# Mo-Kan VW Club

## Valve Cover Racing Rules

### **THE COURSE**

The course shall consist of a launch incline eight feet long, followed by a level run of twenty feet.

The launch incline shall be divided into two lanes, each 18 inches wide. The incline shall be two feet high at the rearmost part and level with the course at the front edge. The front edge shall be mitered so as to provide a smooth transition from the incline to the run out area.

The official "Starting Line" shall be two feet from the rear edge of the incline. A mechanized starting gate will be provided.

The run out section of the course shall consist of two lanes, each 18" wide. The two lanes shall be divided by a strip of wood.

The finish line shall be marked twenty feet from the front edge of the launch incline.

### **THE CARS**

The cars shall have no power source. All motive force is provided by gravity.

Cars shall be based on an actual VW valve cover.

Total length of the car shall not exceed 24".

Wheel track shall not exceed fourteen inches.

Cars shall not exceed FIVE POUNDS in weight!

No movable weights or fluids are allowed.

Cars must have four wheels, each no more than eight inches in diameter.

### **THE RACES**

Cars will run in heats of two cars each.

The cars are to be launched with their front end against the starting gate.

The first car to have its front end cross the finish line is the winner.

If neither car makes it to the finish line, the car going the furthest in its lane wins.

Winning cars will advance to the next round until all are eliminated except one car.

**Good luck to all and we hope to see you racing at the “Bug Blitz, Bus Blast”!**